

K120S / 180S

Food processors

*11,5 and 17,5 lt capacities are a complement to any size catering facility.
Mix and mince quickly and easily to preserve texture and flavour.*



K180S



K120S

- ▶ For the preparation of sauces, mixing and fine and super fine chopping
- ▶ **Process in a matter of seconds** without risk of heating or altering the products
- ▶ **Large bowl capacities** (e.g. mayonnaise):
 - 11,5 lt (K/KE120S) process up to 6 kg
 - 17,5 lt (K/KE180S) process up to 8 kg
- ▶ **Stability guaranteed** during operations thanks to central position of stainless steel bowl
- ▶ Asynchronous motor for **silent** operation and **longer life**
- ▶ Stainless steel mobile stand available as an option
- ▶ Unique scraper/emulsifier to prepare everything from meats to creams





Transparent lid



Touch button control panel

- ▶ Stainless steel bowl with **transparent lid** permits the operator to check the preparation during use
- ▶ **No need to stop the machine during operation.** Ingredients may be added through the opening in the lid
- ▶ Waterproof and user friendly **touch button control** panel
- ▶ Pulse function for **coarse chopping** of large pieces (on 2 speed models)

- ▶ Microtoothed blade rotor, scraper and bowl design ensure **consistent mixing**
- ▶ Thick-walled stainless steel bowl with two handles for **easier movement**
- ▶ Smooth or serrated stainless steel blade rotor (special serrated rotor for meat processing) upon request
- ▶ Models with 2 speeds (1500-3000 rpm) or variable speed (300-3500 rpm)



Stainless steel bowl



Smooth microtoothed emulsifier blade rotor



Bowl scraper



Double safety locking system

- ▶ Transparent lid, bowl and rotor can be easily removed without tools
- ▶ All parts in contact with food are **100% dishwasher safe**



- ▶ Double safety locking system **avoids the risk of spillage** and splashing when lid is opened while rotor is coming to a stop
- ▶ **Safety guaranteed** by magnetic microswitch which stops the machine if lid or bowl are not correctly positioned
- ▶ 3 devices to **ensure operator safety**:
 - 1 hinge sensor when handle is lifted
 - 1 bowl presence sensor
 - 1 cover presence sensor

K120S/KE120S - 11,5 lt capacity

Model	Speed	Phases	Power	RPM
K120S	2 speeds	3 ph	2200 W	1500-3000
KE120S	Variable	1 ph	2200 W	300-3500

External dimensions (wxdxh): 416x680x517mm

K180S/KE180S - 17,5 lt capacity

Model	Speed	Phases	Power	RPM
K180S	2 speeds	3 ph	3600 W	1500-3000
KE180S	Variable	3 ph	3000 W	300-3000

External dimensions (wxdxh): 416x680x603mm